

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT:

PRODUCT NAME: VKB PETROLEUM DRAW OILS

PRODUCT DESCRIPTION: MINERAL BASE CLEANING OIL

PRODUCT CODE: SO-F1

INTENDED USE: Cleaning of industrial mechanical equipment

COMPANY IDENTIFICATION:

VKB PETROLEUM CO. WLL Flat # 1, Building # 2226, Road # 5154, Block # 951 Askar, Bahrain

24 Hour Health Emergency (+973) 999 **Product Technical Information** (+973) 3659 2777 **Supplier General Contact** (+973) 7741 2183

Email info@vkbpetroleum.com

SECTION 2: HAZARDS IDENTIFICATION

OSHA Status: This product is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200)

Physical Hazard: No Specific physical hazard.

Combustible under high temperature

Health Hazard: No adverse health hazard.

May cause irritation to sensitive skins Not intended for human consumption

Environment Hazard: Harmful to aquatic life. Avoid release to the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Petroleum mineral oil lubricant base stock with proprietary performance additives mixtures

| Name | CAS# | Concentration |
|--|-------------|---------------|
| Heavy Hydro treated Naphthalenic Distillates (Petroleum) | 64742-52-5 | 90-98% |
| Additive Mixture | Proprietary | 2-10% |

This product does not contain known hazardous materials at the > 1% level or known carcinogens at the > 0.1% level as defined by 29 CFR 1910.1200

*Exact product composition has been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

GENERAL ADVICE: No specific first aid measures are required. If irritation persists, consult a

medical specialist.

EYE CONTANCT: In case of eye contact, immediately flush eyes with plenty of water for at least

15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if

irritation develops and persists.

SKIN CONTACT: Wash off immediately with soap and plenty of water while removing all

contaminated clothing and shoes. Get medical attention if irritation or allergic

reaction develops and persists.

INHALATION: In case of inhalation of decomposition of products in a fire, symptoms may be

delayed. If inhaled, move to a ventilated place with fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get

medical attention if symptoms occur.

INGESTION: Do NOT induce vomiting. Drink plenty of water. Seek medical attention

immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Symptoms of overexposure to vapors include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

The ingestion of lubricating oils is an unlikely event. No specific therapy is indicated in view of the very low toxicity of the base oil(s) and other components. Treat with supportive measures as appropriate to the patient's condition.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water fog. Carbon dioxide. Foam. Dry chemical product.

UNSUITABLE MEDIA: Use of heavy stream of water

SPECIAL HAZARDS ARISING FROM THE CHEMICAL:

Under fire conditions, hazardous fumes will be present

ADVICE FOR FIRE FIGHTERS: Wear self-contained breathing apparatus, rubber boots and thick rubber

gloves. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Avoid fire-fighting water to enter environment. Promptly isolate the scene by removing all persons in the vicinity of the

incident if there is a fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For Non-Emergency Personnel: Evacuate unnecessary personnel.

For Emergency Responder: Equip cleanup crew with proper protection. Wear suitable

protective clothing, gloves and eye or face protection. Remove

ignition sources.

Environmental Precautions: Contain any spills with dikes or absorbents to prevent migration

and entry into sewers or streams. Avoid release to the

environment. Notify authorities if liquid enters sewers or public

waters.

Methods and materials for **Cleaning and containment:** Clean up any spills as soon as possible, using an absorbent

material to collect it. Use suitable container.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling: Keep away from sources of ignition. No naked lights. No

> smoking. Use only in well ventilated areas. Avoid release to the environment. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with soap and

water before leaving work.

Conditions for safe storage

Store this product in a dry location where it can be protected Including any incompatibilities: from the elements. Store in tightly closed, properly ventilated

containers away from heat, sparks, open flame, strong oxidizers,

radiations and other initiators. Keep at temperature not

exceeding 50°C

Specific end use: Use only as an engine oil.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

| CHEMICAL NAME | ACGIH | | OSHA | |
|---|--------|---------|--------|------|
| CHEWICAL NAIVIE | TLV | STEL | PEL | STEL |
| Heavy Hydrotreated Naphthalenic Distillates | 5mg/m3 | 10mg/m3 | 5mg/m3 | - |
| (Petroleum) | (mist) | (mist) | (mist) | |

Material Safety Data Sheet VKB Petroleum

VKB Flushing Oil

Appropriate Engineering Controls: Good general ventilation should be sufficient to control worker

exposure to airborne contaminants. Emergency shower and

eyewash station.

Environmental exposure Controls: Emissions from ventilation or work process equipment should

be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

levels.

INDIVIDUAL PROTECTION MEASURES

Hygiene measures: Wash hands, forearms and face thoroughly after handling

chemical products, before eating, smoking and using the lavatory and at the end of working period. Appropriate techniques should be use to remove potentially contaminated

clothing. Wash contaminated clothing before using.

Eye/Face Protection: Wear safety glasses with side shields. A face shield may be

necessary under some conditions.

Body Protection: No protective equipment is needed under normal conditions.

For non-routine tasks, personal protection equipment for the body should be selected based on the task being performed and

the risks being involved.

Other Skin Protection: Appropriate footwear and any additional skin protection

measures should be selected based on the task being

performed and the risks involved.

Respiratory Protection: No respiratory protection is normally required. If user operation

generates an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from measured concentrations of this material. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. For air-purifying

respirators, use a particular cartridge.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

| Property | Test | Units | Flushing Oil 15 | Flushing Oil 22 |
|----------|------|-------|-----------------|-----------------|
|----------|------|-------|-----------------|-----------------|

| Density @ 15° C | ASTM D1298 | Kg/m³ | 0.85 | 0.855 |
|-------------------|-------------|-------|------|-------|
| Viscosity @ 40° C | ASTM D445 | mm²/s | 15 | 22 |
| Viscosity Index | ASTM D 2270 | - | 95 | 95 |
| Flash Point | ASTM D93 | °C | 200 | 210 |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No data available

Chemical Stability: Stable under normal conditions

Possibility of hazardous reaction: None under normal conditions

Conditions to avoid: Extremely high or low temperatures

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: None under normal conditions

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects:

Acute toxicity: No specific toxicity data on this product available

Irritation: Not expected to be irritant to eyes or skin

Sensitization: Repeated exposure may cause sensitization due to an allergic

reaction of the skin.

Repeated dose toxicity: No data available

Carcinogenicity: This product contains mineral oils which are considered to be

severely refined and not considered to be carcinogenic under

IARC.

Mutagenicity:Not expected to be mutagenicReproductive toxicity:Not expected to be toxic

<u>Information on likely routes of exposure:</u>

After Ingestion:Ingestion may cause nausea, vomiting, diarrhea.After Inhalation:Inhalation of vapors may cause respiratory irritation.After Skin contact:Prolonged or repeated skin contact with the material will

remove natural oils and could lead to dermatitis.

After Eye contact: Slight eye irritant upon direct contact

Symptoms related to the physical,

chemical and toxicological

characteristics

No adverse health effects were noted.

Delayed and immediate effectsNo adverse health effects were noted.

as well as chronic effects from short and long term exposure

Other toxicological information No data available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: No specific toxicity data on this product available

Persistence and degradability: Major components are inherently biodegradable

Bioaccumulative potential: Not determined

Mobility in soil: It is to be expected small mobility in soil. Some or a few

components may get into the soil and cause pollution of ground

water. Product spreads on the water surface.

Other adverse effects: May contaminate water supply.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods: Dispose in a safe manner with accordance to local/national

regulations.

Product waste: Significant quantities of waste product residues should not be

disposed via the sanitary sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and by-products should at all times comply with the requirements of environmental and waste

disposal legislation and any regional local authority

requirements. Incineration or landfill should only be considered

when recycling is not feasible. Oil collection services are

available for used oil recycling.

SECTION 14: TRANSPORT INFORMATION

General Information: Petroleum Lubricating Oil – Not regulated

Special precautions for user: Transport within user's premise. Always transport in closed

containers that are upright and secure. Ensure that persons transporting the product know what to do in an event of an

accident or spillage.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislations specific for the substance or mixture:

Australian Inventory of Chemical Substances (AICS)

All components are in compliance with chemical notification

requirements in Australia

Canadian Environmental All components are in compliance with the Canadian

Protection Act (CEPA) Environmental Act and are present on the Domestic Substance

List.

European Inventory of Existing Commercial Chemical

Substances (EINECS)

All components listed

USA Toxic Substances Control

Act (TCSA)

All components of this material are on the US TSCA Inventory or

are exempt.

Chemical Safety Assessment Not determined

SECTION 16: OTHER INFORMATION

The information and recommendations contained herein are, to the best of VKB's knowledge and belief, accurate and reliable as of the date issued. The information and recommendations offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to ensure proper health, and safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.